

WOUND FILTER CARTRIDGES FROM FLOWMATIC®



Top quality cartridges for superior depth filtration

Specifications

Specification	Data
Material	FDA grade Polypropylene
Center tubes	Polypropylene
Temperature limit (standard)	140°F (60°C)
Temperature limit (high temp)	200°F (93°C)
Maximum flow rate (5 micron)	5 GPM / 10" length
O.D. (standard cartridges)	2-1/2"
O.D. (Full-Flow cartridges)	4-1/2"

WOUND FILTER CARTRIDGES FROM FLOWMATIC®

Standard 2-1/2" OD cartridges

Product Number	Length	OD	Micron	No. / case
SF1-978	9-7/8"	2-1/2"	1	30
SF5-978	9-7/8"	2-1/2"	5	30
SF20-978	9-7/8"	2-1/2"	20	30
SF50-978	9-7/8"	2-1/2"	50	30
SF1-20	20"	2-1/2"	1	15
SF5-20	20"	2-1/2"	5	15
SF20-20	20"	2-1/2"	20	15
SF50-20	20"	2-1/2"	50	15
SF1-30	30"	2-1/2"	1	15
SF5-30	30"	2-1/2"	5	15
SF20-30	30"	2-1/2"	20	15
SF50-30	30"	2-1/2"	50	15
SF1-40	40"	2-1/2"	1	10
SF5-40	40"	2-1/2"	5	10
SF20-40	40"	2-1/2"	20	10
SF50-40	40"	2-1/2"	50	10

Full-Flow (BB) 4-1/2" OD cartridges

Product Number	Length	OD	Micron	No. / case
SF1-10-425	9-3/4"	4-1/2"	1	8
SF5-10-425	9-3/4"	4-1/2"	5	8
SF20-10-425	9-3/4"	4-1/2"	20	8
SF50-10-425	9-3/4"	4-1/2"	50	8
SF1-20-425	20"	4-1/2"	1	4
SF5-20-425	20"	4-1/2"	5	4
SF20-20-425	20"	4-1/2"	20	4
SF50-20-425	20"	4-1/2"	50	4

Wound cartridges with 304 stainless steel center tubes for temperatures to 200°F (93°C)

Product Number	Length	OD	Micron	No. / case
MS10FS5	9-7/8"	2-1/2"	5	30
MS10FS20	9-7/8"	2-1/2"	20	30
MS10FS50	9-7/8"	2-1/2"	50	30
MS20FS5	20"	2-1/2"	5	15
MS20FS20	20"	2-1/2"	20	15
MS20FS50	20"	2-1/2"	50	15
MS30FS5	30"	2-1/2"	5	15
MS310FS20	30"	2-1/2"	20	15
MS30FS50	30"	2-1/2"	50	15
MS40FS5	40"	2-1/2"	5	10
MS40FS20	40"	2-1/2"	20	10
MS40FS50	40"	2-1/2"	50	10